

2022

SUMMIT® X® WITH EXPERT PACKAGE

The ultimate deep-snow sled with features sharpened for technical terrain riding.



SUMMIT® X® WITH EXPERT PACKAGE
165 850 E-TEC® TURBO SHOWN

// WHAT'S NEW

- Standard with two sets of LinQ attachment points

// PACKAGE HIGHLIGHTS

- Two *ULTIMATE* color options with panel wrap: supreme look and finish, maximum protection
- Rotax® 850 E-TEC® or 850 E-TEC Turbo engines available
- Premium shock package with stiffer calibration
- Short tunnel with lightweight snowflap
- RAS™ 3 front suspension with lightweight ski spindle and revised ski stopper
- tMotion™ rear suspension with ice scratchers and adjustable limiter strap
- E-TEC® SHOT™ starter standard
- Full-length extruded-profile running boards with large openings
- One-piece lightweight hood on all models
- Flexible handguards
- Short riser block (120 mm)
- Sea-level calibration
- 4.5 in. digital display
- Smaller-diameter handlebar ends and handgrips
- Ultra-compact and lightweight deep-snow seat
- DS 3 skis
- Belt monitoring system

ROTAX® ENGINE	850 E-TEC® TURBO	850 E-TEC®
Engine details	Liquid-cooled, two-stroke, turbocharged, eRAVE™	Liquid-cooled, two-stroke, eRAVE™
Horsepower	165 up to 2.44 km	165
Cylinders – Displacement	2 – 849 cc	2 – 849 cc
Bore – Stroke	82 mm – 80.4 mm	82 mm – 80.4 mm
Carburation	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection with additional booster injectors
Fuel type – Octane	Unleaded – 95	Unleaded – 95
Fuel tank	36 L	36 L
Oil tank capacity	3.4 L	3.4 L

POWERTRAIN		
Drive clutch	pDrive™ with clickers	pDrive™ with clickers
Driven clutch	QRS Vent Plus	QRS Vent Plus
Drive sprocket pitch	89 mm	89 mm

DIMENSIONS	
Overall vehicle length	3,188 mm (154 in.) 3,299 mm (165 in.)
Overall vehicle width	1,080 to 1,110 mm
Overall vehicle height	1,306 mm
Ski stance	910 or 950 mm
Track	PowderMax® Light
(Length x Width x Profile)	154 x 16 x 3.0 in. 165 x 16 x 3.0 in.

COLOR	
<i>ULTIMATE</i> Liquid Titanium / Carbon Black	
<i>ULTIMATE</i> Triple Black	

SUSPENSION	
Front suspension	RAS™ 3
Front shock	HPG™ Plus with lightweight springs
Front suspension travel	215 mm
Rear suspension	tMotion™ with adjustable limiter strap
Center shock	HPG™ Plus with lightweight spring
Rear shock	KYB® PRO 36 Easy-Adjust
Rear suspension travel	239 mm (154, 165 in.)

FEATURES	
Frame	REV® Gen4
Bodywork	Narrow design
Skis	Pilot™ DS 3
Seating	Deep-snow ultra-compact and lightweight
Handlebar	Tapered U-shaped aluminum with J-hooks/ Low grab handle/Flexible handguards
Riser block height	120 mm
Starter	SHOT
Reverse	RER™
Air radiator	
Brake system	Brembo racing brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	Optional
Runner – Carbide	Square 3/8 – 102 mm
Bumpers (front/rear)	Std/Std

