SKANDIC° LE
The perfect snowmobile for hardworking off-trail performance.

// PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ engine
- Available with 20 in. or 24 in. track options
- KYB† 36 rear shock
- Multi-LinQ plate with 125 lb/56.7 kg cargo capacity
- 4.5 in. digital display
- LTS telescopic front suspension
- SC[†]-5U articulating rear suspension with locking mechanism (no tool required)
- Ultra large LinQ utility cargo box with 135 L/35.7 US gal of storage
- Ultra high windshield with side deflectors
- Removable passenger seat with grips
- Hitch
- · Air radiator with fan
- Standard electric start
- Deep-snow running boards with large openings
- Easy-shift transmission (H-L-N) with RER™/ electro-mechanical reverse (4-stroke)

SKANDIC LE 900 ACE SHOWN

- Pivoting mirrors
- pDrive™ clutch
- Low handlebar strap
- Pilot™ 7.4 skis

ROTAX ENGINE	900 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders -	3
Displacement	899 cc
Bore – Stroke (mm)	73 - 69.7
Carburation	EFI
Fuel type – Octane	Unleaded - 95
Fuel tank (L/US gal)	42/11.1
Oil tank capacity (L/qt)	3.3/3.5
POWERTRAIN	
Drive clutch	pDrive
Driven clutch	QRS
Drive sprocket pitch (mm/in.)	73/2.86
DRY WEIGHT	
Dry weight 20 in track (kg/lb)	281/620
Dry weight 24 in track (kg/lb)	298/657

DIMENSIONS

Vehicle overall length (mm/in.)	3,222/126.9
Vehicle overall width (mm/in.)	1,089/42.8
Vehicle overall height (mm/in.)	1,513/59.6
Ski stance (mm/in.)	889 / 35
Available Tracks (in.) (Length x Width x Profile)	Silent Cobra WT: 154 x 20 x 1.5 Silent Cobra SWT: 154 x 24 x 1.5 (opt.)

SUSPENSION

JUJI LIIJIUII	
Front suspension	LTS
Front shock	Motion Control
Front suspension travel (mm/in.)	150 5.9
Rear suspension	SC-5U
Center shock	Motion Control
Rear shock	KYB 36
Rear suspension travel (mm/in.)	239/9.4

COLOR

FEATURES

FEATURES	
Platform	REV® Gen4
Headlights	Halogen
Skis	Pilot 7.4
Seating	WideTrack 2-up
Handlebar	Standard with J-hooks/ Grab handle
Riser block height (mm/in.)	145/5.7
Starter	Electric
Reverse	Electro-mechanic
Air radiator	High-efficiency w/ fan
Brake system	Brembo [†]
Heated throttle lever/grips	Standard (driver only)
Gauge type	4.5 in. digital
Windshield	Ultra-high with mirrors
Runner (In.) – Carbide (In.)	3/8 square - 4
Bumpers (front/rear)	Heavy Duty/Hitch

ski-doo.

