2024

SUMMIT ADRENALINE

An excellent deep-snow machine for any rider.



// WHAT'S NEW • Rotax® 600R E-TEC® engine available

// PACKAGE HIGHLIGHTS

- Rotax 850 E-TEC engine
- REV® Gen5 platform
- tMotion™ X rear suspension
- LED headlights

- Narrower running boards and bodywork
- High quality KYB† shock package
- RAS™ 3 front suspension with lightweight ski spindle and revised ski stopper
- Deep snow running boards with large openings
- Glove box with 3.5 L of storage
- Low handlebar strap
- Pilot™ DS 3 skis
- Belt monitoring system

ROTAX ENGINE	850 E-TEC	600R E-TEC
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, two-stroke, eRAVE
Cylinders – Displacement	2 - 849 cc	2 - 599.4 cc
Bore – Stroke (mm)	82 - 80.4	72.3 – 73
Carburation	E-TEC direct injection with additional booster injectors	E-TEC direct injection
Fuel type – Octane	Unleaded – 95	Unleaded – 95
Fuel tank (L/US gal)	36/9.5	36/9.5
Oil tank capacity (L/qt)	3.4/3.6	3.4/3.6
POWERTRAIN		
Drive clutch Driven clutch	pDrive™ with clickers QRS Vent Plus	pDrive™ with clickers QRS Vent
Drive sprocket pitch (mm/in.)	73/2.86 (146 in.) 89/3.5 (154 in.)	73/2.86 (146 in.) 89/3.5 (154 in.)
DRY WEIGHT		
Dry weight (kg/lb)	203/447 (146 in.) 201/443 (154 in.)	196/432 (146 in.) 194/428 (154 in.)
DIMENSIONS		
Vehicle overall length (mm/in.)	3,208/122.4 (146 in.) 3,318/130.6 (154 in.)	
Vehicle overall width (mm/in.)	1,073/42.2 (adjustable)	
Vehicle overall height (mm/in.)	1,395/54.9	
Ski stance (mm/in.)	930/36 (adjustable)	
Available Tracks (in.) (Length x Width x Profile)	PowderMax II with FlexEdge: 146 x 16 x 2.5	
	PowderMax Light with FlexEdge:	
	154 x 16 x 2.5	

Catalyst Grey / Neo Yellow	
SUSPENSION	
Front suspension	RAS 3
Front shock	KYB 36
Front suspension travel (mm/in.)	215/8.5
Rear suspension	tMotion X
Center shock	KYB 36
Rear shock	KYB 36
Rear suspension travel (mm/in.)	258/10.2
FEATURES	
Platform	REV Gen5
Headlights	High-performance LED
Skis	Pilot DS 3
Seating	Deep snow
Handlebar	Tapered with J-hooks/Grab handl
Riser block height (mm/in.)	165/6.5
Starter	Electric
Reverse	RER™
Brake system	Brembo [†]
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital
	0-4:1
Windshield	Optional
Windshield Runner (in.) – Carbide (in.)	υρτίσηαι 3/8 square – 4



